



RH/RA Direct Drive C-Clamp Portable Mixers

The RH/RA Series feature oversized bearings, couplings and a mounting clamp. They feature large sealed ball bearings on the output shaft to absorb the side loads.

These mixers are recommended for blending 50 to 1,000 gallon tanks and applications where high shear and moderate flow are required.

Shaft speed is 1750 RPM.

Square pitch propellers are standard

FEATURES

- 100% Process Guarantee
- 3 Year Mechanical Warranty
- All Motors are Standard NEMA C-Face Design
- C-Clamp Mount or Optional Cup Plate Mount
- Impellers and Shafts are 316SS
- Coatings (PVC, Rubber/Others on Request)
- USDA Sanitary Versions Available
- OSHA Approved for Safety
- Maintenance Free for 3 Years

MOTORS

- 115/230/1/60 or 208/230/460/3/60, TEFC, TEXP, Chemical Duty, Washdown, High Efficiency
- 50Hz and Special Voltages Available
- Air Motors – 1, 2 HP
- AC & DC Variable Speed Drives



	MODEL	NET WT. (Lbs)	SHAFT RPM	HP	STD. SHAFT (Inches)	STD. PROP DIA. (Inches)	
						Single	Dual
Electric	RH-1	42	1750	¼	¾ x 36	3.5	3.5
	RH-2	48		1/3		4	4
	RH-3	55		½	¾ x 48	5	5
	RH-5	72		1		6	5
	RH-7	77		2	¾ x 48	7	7
	RH-8	82		3	1 x 48	7	8
Air	RA-5	59	170-1800	1	1 x 60	6	5
	RA-7	75		2		7	6